G50-100 Polyethylene Copolymer

G50-100 is a high molecular weight, high density polyethylene copolymer developed for sheet extrusion, thermoforming, and large part blow molding where the finished product demands outstanding physical performance. This material meets the Food and Drug Administration requirements of 21 CFR 177.1520.

Typical Properties¹

	Values		ASTM
	English Units	SI Units	Method
Resin	-		
Density	—	0.950 g/cc	D4883
Melt Index 190 C/21.6 kg	—	10.0 g/10 min	D1238
Compression Molded Samples			
Tensile Strength (2 in/min)			D638
@ Yield	3,750 psi	26.1 MPa	
@ Break	5,200 psi	36.0 MPa	
Elongation (2 in/min)	-		D638
@ Yield	10%	10%	
@ Break	920%	920%	
Flexural Modulus			D790A
Tangent Method	177,000 psi	1,220 MPa	
2% Secant Method	137,300 psi	950 MPa	
Notched Izod Impact Strength	7.7 ft-lbf/in	40.5 kJ/m^2	D256
Hardness		-	D2240
Shore D	67	67	
Vicat Softening Point	259 F	126 C	D1525
Brittleness Temperature	<-103 F	<-75 C	D746
Heat Deflection Temperature			D648
@ 66 psi (455 kPa)	161 F	72 C	
Environmental Stress Crack Resistance	e		D1693
Condition B, 100% Igepal, F50 (hrs.)	264	264	
Oxidation Induction Time			D3895
@ 210 C	>21 min	>21 min	

¹ Properties will vary and are not to be used for specification purposes.

The name and logo INEOS are trademarks of the INEOS Group and its affiliated companies and businesses

2600 South Shore Boulevard, Ste. 500 League City, TX 77573 Tel: 281-535-6600 www.incos-op.com



Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. As conditions of use may vary and are beyond the control of INEOS Olefins & Polymers USA, no representations or warranty, express or implied, are made with respect to the accuracy, reliability, or completeness of this information. This information in no way modifies, amends, enlarges, or creates any specification or warranty, and ALL WARRANTIES, EXPRESS OR IMPLED, INCLUDING WITHOUT LIMITATION THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE HEREBY EXCLUDED. INEOS Olefins & Polymers USA shall not be responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate gractices, or from hazards inherent in the nature of the product and/or material designated and may not be valid for such product and/or material used in combination with any other product and/or material especified. This information shall not be construed as a recommendation for any use that may infringe any patent, trademark, or the like, or as an endorsement of any material, equipment, service, or other item not supplied by INEOS Olefins & Polymers USA.

Regulatory Information

The product and uses described herein may require global product registrations and notifications for chemical inventory listings, or for use in food contact or medical devices. For further information, call + 1-800-527-5419.

Health and Safety Information

The product described herein may require precautions in handling and use because of toxicity, flammability, or other consideration. The Material Safety Data Sheet (MSDS) contains the available product health and safety information for this material and can be found at **www.ineos-op.com**. Before using any material, a customer is advised to consult the MSDS for the product under consideration for use.

The Material Safety Data Sheet for this product contains shipping descriptions and should be consulted, before transportation, as a reference in determining the proper shipping description. If the material shipped by INEOS is altered or modified, different shipping descriptions may apply and the MSDS of the original material should not be used.

For additional information, samples, pricing and availability, please contact:

INEOS Olefins & Polymers, USA

Marina View Building 2600 South Shore Boulevard Suite 500 League City, Texas 77573 Phone: +1 281 535 6600 Fax: +1 281 535 6764 Customer Service: +1 800 527 5419 Tech Service: +1 800 338 0489 www.ineos-op.com

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. As conditions of use may vary and are beyond the control of INEOS Olefins & Polymers USA, no representations or warranty, express or implied, are made with respect to the accuracy, reliability, or completeness of this information. This information in no way modifies, amends, enlarges, or creates any specification or warranty, and ALL WARRANTIES, EXPRESS OR IMPLED, INCLUDING WITHOUT LIMITATION THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE HEREBY EXCLUDED. INEOS Olefins & Polymers USA shall not be responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate described herein. This information relates only to the specific product and/or material designated and may not be valid for such product and/or material used in combination with any other product and/or material, equipment, service, or other item not supplied by INEOS Olefins & Polymers USA.

The name and logo INEOS are trademarks of the INEOS Group and its affiliated companies and businesses.



