B50-35H-176 is a high density polyethylene copolymer developed for blow molding. It is recommended for use in applications which require a combination of high top load strength and good environmental stress crack resistance (ESCR). This material contains a fully FDA sanctioned antistat and meets the Food and Drug Administration requirements of 21CFR 177.1520.

Typical Properties¹

| | Values | | ASTM |
|---------------------------------------|----------------------|-----------------------|--------|
| | English Units | SI Units | Method |
| Resin | | | |
| Density | _ | 0.951 g/cc | D4883 |
| Melt Index 190°C/2.16 kg | — | 0.35 g/10 min | D1238 |
| Compression Molded Samples | | | |
| Tensile Strength (2 in/min) | | | D638 |
| @ Yield | 3,700 psi | 25.5 MPa | |
| @ Break | 3,000 psi | 18.6 MPa | |
| Elongation (2 in/min) | - | | D638 |
| @ Yield | 10% | 10% | |
| @ Break | >600% | >600% | |
| Flexural Modulus | | | D790A |
| Tangent Method | 180,000 psi | 1,116 MPa | |
| 2% Secant Method | 135,000 psi | 837 MPa | |
| Notched Izod Impact Strength | 2.75 ft-lbf/in | 14.4 kJ/m^2 | D256 |
| Hardness (Shore D) | 64 | 64 | D2240 |
| Vicat Softening Point | 257 F | 125 C | D1525 |
| Brittleness Temperature | <-103 F | <-75 C | D746 |
| Heat Deflection Temperature | | | D648 |
| @ 66 psi (455 kPa) | 162 F | 72 C | |
| @ 264 psi (1,820 kPa) | 113 F | 45 C | |
| Environmental Stress Crack Resistance | 2 | | D1693 |
| Condition B, 100% Igepal F50 (hrs.) | 40 hrs | 40 hrs | |

¹ Properties will vary and are not to be used for specification purposes.

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. As conditions of use may vary and are beyond the control of INEOS Olefins & Polymers USA, no representations or warranty, express or implied, are made with respect to the accuracy, reliability, or completeness of this information. This information in no way modifies, amends, enlarges, or creates any specification or warranty, and ALL WARRANTIES, EXPRESS OR IMPLED, INCLUDING WITHOUT LIMITATION THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE HEREBY EXCLUDED. INEOS Olefins & Polymers USA shall not be responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices, or from hazards inherent in the nature of the product and/or material and for toxicological effects or Industrial Hygiene associated with particular use of any product described herein. This information relates only to the specific product and/or material designated and may not be valid for such product and/or material used in combination with any other product and/or material or in any process, unless otherwise specified. This information shall not be construed as a recommendation for any use that may infringe any patent, trademark, or the like, or as an endorsement of any material, equipment, service, or other item not supplied by INEOS Olefins & Polymers USA.

The name and logo INEOS are trademarks of the INEOS Group and its affiliated companies and businesses.

2600 South Shore Boulevard, Ste. 500 League City, TX 77573 Tel: 281-535-6600 www.ineos-op.com



Regulatory Information

The product and uses described herein may require global product registrations and notifications for chemical inventory listings, or for use in food contact or medical devices. For further information, call + 1-800-527-5419.

Health and Safety Information

The product described herein may require precautions in handling and use because of toxicity, flammability, or other consideration. The Material Safety Data Sheet (MSDS) contains the available product health and safety information for this material and can be found at **www.ineos-op.com**. Before using any material, a customer is advised to consult the MSDS for the product under consideration for use.

The Material Safety Data Sheet for this product contains shipping descriptions and should be consulted, before transportation, as a reference in determining the proper shipping description. If the material shipped by INEOS is altered or modified, different shipping descriptions may apply and the MSDS of the original material should not be used.

For additional information, samples, pricing and availability, please contact:

INEOS Olefins & Polymers, USA

Marina View Building 2600 South Shore Boulevard Suite 500 League City, Texas 77573 Phone: +1 281 535 6600 Fax: +1 281 535 6764 Customer Service: +1 800 527 5419 Tech Service: +1 800 338 0489 www.ineos-op.com

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. As conditions of use may vary and are beyond the control of INEOS Olefins & Polymers USA, no representations or warranty, express or implied, are made with respect to the accuracy, reliability, or completeness of this information. This information in no way modifies, amends, enlarges, or creates any specification or warranty, and ALL WARRANTIES, EXPRESS OR IMPLED, INCLUDING WITHOUT LIMITATION THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE HEREBY EXCLUDED. INFOS Olefins & Polymers USA shall not be responsible for any damage or injury resulting from abnormal use, from any failure to follow appropriate practices, or from hazards inherent in the nature of the product and/or material, nor for toxicological effects or Industrial Hygiene associated with particular use of any product described herein. This information relates only to the specific product and/or material designated and may not be valid for such product and/or material used in combination with any other product and/or material, or in any process, unless otherwise specified. This information shall not be construed as a recommendation for any use that may infringe any patent, trademark, or the like, or as an endorsement of any material, equipment, service, or other item not supplied by INEOS Olefins & Polymers USA.

The name and logo INEOS are trademarks of the INEOS Group and its affiliated companies and businesses.



2600 South Shore Boulevard, Ste. 500 League City, TX 77573 Tel: 281-535-6600 www.ineos-op.com